



NOTE: RH ASSEMBLY SHOWN
 ASSEMBLE WITH CRANK ADJUSTMENT
 ON OPERATOR SIDE

INDICATOR SUB ASSY

1. PRESS OIL BRG #39 INTO PLATE #37
2. INSERT THREADED ROD LEAVING END OUT 3"
3. DRILL COLLARS 90° FROM SET SCREW & PIN TO ROD W/ 3/16"x1" ROLL PIN
4. INSERT IND. & LOCK DOWN W/ SET SCREW
5. DRILL AND PIN HANDLE W/ 3/16"x1" ROLL PIN

NOTE: UNLESS OTHERWISE SPECIFIED BREAK ALL SHARP EDGES DEVIATIONS FROM THIS DRAWING MUST BE ADDRESSED WITH COMBI PACKAGING SYSTEMS LLC	MATERIAL SEE B/M		FINISH -		DESCRIPTION Assy - Upper FC 3M 2" 0-25 Cat. 1 & 3				
	TOLERANCES (UNLESS OTHERWISE SPECIFIED) .000 = b .003 .00 = b .010 ANGLES = b 1/2 FRACTION = b 1/64		NOTE: THIS DRAWING IS NOT TO BE REPRODUCED OR COPIED WITHOUT CONSENT FROM COMBI PACKAGING SYSTEMS		DRAWN BY sbeatty	DRAFT DATE 05/21/07	SCALE 3/16:1		
					CHECKED BY	CHECK DATE	SIZE B	DWG NO TB10500345.01	Sheet 1 of 1